

BETONLÖSER

Liquid cleaning agent for removing concrete and cement residues

Item No 1100

FIELDS OF APPLICATION

BETONLÖSER is a liquid product for the elimination of concrete and cement residues on brick and clinker brick fronts and other building parts.

APPLICATION QUANTITY

The application quantity depends on the surface structure, its absorbency and its contamination level and needs to be determined in each individual case.

PROCESSING INDICATIONS

BETONLÖSER is diluted to a ratio of 1:2 to 1:5. The watery solution is then applied by brush or broom. Finally, the cleaned surfaces are thoroughly washed with clean water.

This product is classified as hazardous according to the CLP regulations. See safety data sheet for further information.

PACKAGING

- 30 l can
- 200 l barrel
- 1000 l container

WORKING PRINCIPLE

BETONLÖSER is particularly suited for removing concrete and cement residues from washed concrete elements.

TECHNICAL DATA

Homogeneity	homogenous
Colour	light yellowish
State	liquid
Density	1.19 ± 0.03 g/cm ³
Workability	from +1 °C
Shelf life	approx. 1 year from date of production if stored properly
Storage conditions	Store in unopened, original sealed packaging between +5 °C and +25 °C. Protect from frost and insolation.

REMARKS

The information describes the application- and processing possibilities of a product and its operation principles under regular conditions. Having no influence on the further application and processing, especially in conjunction with other construction materials, the given indication is neither a warranty in respect of the product's properties or its fitness for a particular purpose nor a full instruction of use.

This information, any other recommendation or verbal advice are not binding and do not infer to any liability or legal demand.

Due to continuous further development, the most recent Technical Data Sheet is valid and will be supplied on request. All orders are accepted subject to our current general terms and conditions.

Edition: 29 March 2023

SUITABILITY- AND PRE-TESTS ARE NECESSARY BEFORE APPLYING THE CONCRETE ADMIXTURE!