Revision: 22.07.2019

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.07.2019

Version number 1.03

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier

- Trade name: PROTECT PRIMER neo

- Article number: 2762

- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Application of the substance / the mixture concrete protection

- 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier:

Ha-Be Betonchemie GmbH

Stuevestrasse 39

31785 HAMELN, GERMANY

- Further information obtainable from: info@ha-be.com
- 1.4 Emergency telephone number:

0049 5151 587-0

Only available during office hours.

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms





GHS02 GHS07

- Signal word Danger
- Hazard-determining components of labelling:

1-methoxy-2-propanol

n-butyl acetate

propan-2-ol

- Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

(Contd. on page 2)

(Contd. of page 1)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.07.2019 Version number 1.03 Revision: 22.07.2019

Trade name: PROTECT PRIMER neo

P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON ČENTER/doctor/x/if you feel unwell. P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use for extinction: Foam.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Chemical characterisation: Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.

- Dangerous components:		
	n-butyl acetate	10-25%
EINECS: 204-658-1	🊸 Flam. Liq. 3, H226; 🐠 STOT SE 3, H336	
CAS: 107-98-2	1-methoxy-2-propanol	10-25%
EINECS: 203-539-1	♦ Flam. Liq. 3, H226; ♦ Acute Tox. 3, H331; ♦ STOT SE 3, H336	
CAS: 67-63-0	propan-2-ol	10-25%
EINECS: 200-661-7	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336	
		2.5-10%
EINECS: 204-626-7	🚸 Flam. Liq. 3, H226; 🐠 Eye Irrit. 2, H319	

⁻ Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures

- After inhalation:

Supply fresh air; consult doctor in case of complaints.

Take affected persons into fresh air and keep quiet.

- After skin contact:

Take-off and remove wetted clothing, shoes and stocking immediately. Wash any exposed body surfaces with soap and water.

- After eve contact:

Seek immediate medical advice.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Call a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

- GE

according to 1907/2006/EC, Article 31

Printing date 22.07.2019 Version number 1.03 Revision: 22.07.2019

Trade name: PROTECT PRIMER neo

(Contd. of page 2)

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

The inhalation of vapour and fume may cause breathlessness. Otherwise it may result in irration of respiratory system.

- 5.3 Advice for firefighters
- Protective equipment: Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

- 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling

Store in cool, dry place in tightly closed receptacles.

Take note of emission threshold.

Use solvent-proof equipment.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about fire - and explosion protection:

Use explosion-proof apparatus / fittings and spark-proof tools.

Highly volatile, flammable constituents are released during processing.

Fumes can combine with air to form an explosive mixture.

Wear shoes with conductive soles.

Emergency cooling must be available in case of nearby fire.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities

- Storage:

- Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Store in a cool location.

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Store in well ventilated conditions with a temperature between 5 and 25°C.

Protect from exposure to the light.

Keep container tightly sealed.

(Contd. on page 4)

according to 1907/2006/EC, Article 31

Printing date 22.07.2019 Version number 1.03 Revision: 22.07.2019

Trade name: PROTECT PRIMER neo

(Contd. of page 3)

Store in cool, dry conditions in well sealed receptacles.

-7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:
mg. carerie mini raidos matroquire membras at are memprasor
122 96 4 m butul contato

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

107-98-2 1-methoxy-2-propanol

AGW Short-term value: 370 mg/m³, 100 ppm WEL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

123-42-2 4-hydroxy-4-methylpentan-2-one

WEL Short-term value: 362 mg/m³, 75 ppm Long-term value: 241 mg/m³, 50 ppm

- Regulatory information WEL: EH40/2018
- Additional information: The lists valid during the making were used as basis.
- 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

according to 1907/2006/EC, Article 31

Printing date 22.07.2019 Version number 1.03 Revision: 22.07.2019

Trade name: PROTECT PRIMER neo

- Penetration time of glove material

(Contd. of page 4)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties

- General Information

- Appearance:

Form: Fluid

Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 pH-value: Not determined.

- Change in condition

Melting point/freezing point: Undetermined.
Initial boiling point and boiling range: Undetermined.

- Flash point: 17 °C (DIN 53213)

Not applicable.

- Flammability (solid, gas): Not applicable.

- Ignition temperature: 270 °C

- **Decomposition temperature:** Not determined.

- Explosive properties: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

- Explosion limits:

Lower:
Upper:
73 Vol %
73 Vol %

- Vapour pressure at 20 °C:
16 hPa

- Density at 20 °C:
20.89 g/cm³
Not determine

- Vapour density- Evaporation rateNot determined.Not determined.

- Solubility in / Miscibility with

water: Partly miscible.- Partition coefficient: n-octanol/water: Not determined.

- Viscosity:

Dynamic: Not determined. **Kinematic at 20 °C:** 14 s (DIN 53211/4)

- Solvent content:

Organic solvents: 70.0 %

- **9.2 Other information** No further relevant information available.

GB

according to 1907/2006/EC, Article 31

Printing date 22.07.2019 Version number 1.03 Revision: 22.07.2019

Trade name: PROTECT PRIMER neo

(Contd. of page 5)

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions

Reacts with strong acids and alkali.

Reacts with strong oxidising agents.

- 10.4 Conditions to avoid At elevated temperatures hazardous decomposition products may be evolved.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

Carbon monoxide

Nitrogen oxides (NOx)

Possible in traces.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation

Causes serious eye irritation.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

GB

according to 1907/2006/EC, Article 31

Printing date 22.07.2019 Version number 1.03 Revision: 22.07.2019

Trade name: PROTECT PRIMER neo

(Contd. of page 6)

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- 14.1 UN-Number

- ADR, IMDG, IATA UN1263

- 14.2 UN proper shipping name

- **ADR** 1263 PAINT RELATED MATERIAL PAINT RELATED MATERIAL

- 14.3 Transport hazard class(es)

- ADR



- Class 3 Flammable liquids.

- IMDG, IATA



- Class 3 Flammable liquids.

- Label 3

- 14.4 Packing group

- ADR, IMDG, IATA ||

- 14.5 Environmental hazards:

- Marine pollutant: No

- 14.6 Special precautions for user Warning: Flammable liquids.

- EMS Number: F-E,S-E
- Stowage Category B
- 14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

- Transport/Additional information: Not dangerous according to the above specifications.

- ADR

- Limited quantities (LQ) 5L - Excepted quantities (EQ) Code: E2

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

- Tunnel restriction code

............

- IMDG

- Limited quantities (LQ) 5L - Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

(Contd. on page 8)

according to 1907/2006/EC, Article 31

Printing date 22.07.2019 Version number 1.03 Revision: 22.07.2019

Trade name: PROTECT PRIMER neo

(Contd. of page 7)

- UN "Model Regulation": UN 1263 PAINT RELATED MATERIAL, 3, II

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The above information describes exclusively the safety requirements of the product(s) and is based on our present-day knowledge. It does not represent a guarantee for the properties of the product(s) described in terms of the legal warranty regulations. Properties of the product are to be found in the respective product leaflet.

- Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H336 May cause drowsiness or dizziness.

- Abbreviations and acronyms:

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 3: Acute toxicity - Category 3

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3