

PANTARHIT® 530 (BV)

Item No 0183

Plasticizer acc. to EN 934-2 for producing concrete applied in traffic areas

PANTARHIT® 530 (BV) is also suitable as superplasticizer/ retarder for concrete

FIELDS OF APPLICATION

PANTARHIT® 530 (BV) is a robust plasticizer for the production of concrete applied in traffic areas. The product enables precise adjustment of the desired consistency according to the type of installation.

Furthermore PANTARHIT® 530 (BV) offers the following benefits:

- High mix stability
- Good consistency maintenance
- Fast dispersion
(may lead to shorter mixing times)
- Improved workability
- Improved evenness
- Special suitability for air-entrained concretes
- Reduced viscosity

Besides PANTARHIT® 530 (BV) shows an excellent robustness against varying aggregates and changing water contents.

These characteristics provide ready-mix producers with high application reliability.

DOSAGE

Recommended dosage range 0.2 – 2.3 mass-% of the cement content;
is equivalent to 2 – 20 ml per kg cement.

WORKING PRINCIPLE

PANTARHIT® 530 (BV) improves the cement dispersion within the concrete significantly. This property allows the formation of a homogenous and low-viscosity cement paste which ensures an improved workability and facilitates the compaction of concrete.

PANTARHIT® 530 (BV) advances the placing of concrete and improves its processing and compaction significantly.

TECHNICAL DATA

Homogeneity	homogenous
Colour	brown
State	liquid
Density	1.15 ± 0.02 g/cm ³
pH-value	5.0 ± 1.0
Chloride content	< 0.10 mass-%
Alkali content (Na ₂ O equivalent)	< 4.5 mass-%
Workability	from +1 °C
Shelf life	approx. 1 year from date of production of stored properly
Storage conditions	Store in unopened, original sealed packaging between +5 °C and +25 °C. Protect from frost and insolation.

PROCESSING INDICATIONS

PANTARHIT® 530 (BV) should be added to the ready-mixed concrete.

The mixing time must comply with the regulations defined in DIN EN 206-1.

This product is not classified as hazardous according to the CLP regulations. See safety data sheet for further information.

PACKAGING

- 30 l can
- 200 l barrel
- 1000 l container
- loose by bulk supply

REMARKS

This information describes the application- and processing possibilities of a product and its operation principles under regular conditions. Having no influence on the further application and processing, especially in conjunction with other construction materials, the given indication are neither a warranty in respect of the product's properties or its fitness for a particular purpose nor a full instruction of use. This information, any other recommendation or verbal advice are not binding and do not infer to any liability or legal demand.

Due to continuous further development, the most recent Technical Data Sheet is valid and will be supplied on request. All orders are accepted subject to our current general terms and conditions.

Edition: 15 January 2021

SUITABILITY- AND PRE-TESTS ARE NECESSARY BEFORE APPLYING THE CONCRETE ADMIXTURE!