

## PANTARHIT® 35 (BV)

**Plasticizer for concrete acc. to EN 934-2**

Item No 0101

### FIELDS OF APPLICATION

PANTARHIT® 35 (BV) is a plasticizer for producing F3 consistency concrete in ready-mixed concrete plants and has a slight retarding effect.

PANTARHIT® 35 (BV) can transform plastic concrete (F2) into soft concrete (F3) without impairing the water/cement ratio (is equivalent to S2 into S3).

### DOSAGE

Recommended dosage range 0.2 – 0.9 mass-% of the cement content;  
is equivalent to 2 – 7.5 ml per kg cement.

#### For F3 concrete | $\alpha = 480$ mm

Having an initial consistency at the end of F2: approx. 3 ml per kg cement.

### PROCESSING INDICATIONS

PANTARHIT® 35 (BV) should be added either with the tempering water or to the premixed concrete.

This product is not classified as hazardous according to the EC directives, regulations on hazardous substances and forwarding instructions. The generally accepted precautions for handling chemicals must be followed. The corresponding Material Safety Data Sheet is available upon request.

### PACKAGING

- 30 l can
- 200 l barrel
- 1000 l container
- loose by bulk supply

### WORKING PRINCIPLE

PANTARHIT® 35 (BV) causes a high plasticizing effect by reducing the surface tension of the water. Thus a high water saving potential and an increased pressure strength is achieved.

Concretes produced with PANTARHIT® 35 (BV) can more easily be pumped, placed, levelled and compacted.

### TECHNICAL DATA

Homogeneity	homogenous
Colour	brown
State	liquid
Density	$1.21 \pm 0.03 \text{ g/cm}^3$
pH-value	$5 \pm 1$
Chloride content	< 0.10 mass-%
Alkali content (Na <sub>2</sub> O equivalent)	< 1.0 mass-%
Workability	from +1 °C
Shelf life	approx. 1 year from date of production if stored properly
Storage conditions	Store in unopened, original sealed packaging between +5 °C and +25 °C. Protect from frost and insolation.

## REMARKS

---

This information describes the application- and processing possibilities of a product and its operation principles under regular conditions. Having no influence on the further application and processing, especially in conjunction with other construction materials, the given indication are neither a warranty in respect of the product's properties or its fitness for a particular purpose nor a full instruction of use.

This information, any other recommendation or verbal advice are not binding and do not infer to any liability or legal demand.

Due to continuous further development, the most recent Technical Data Sheet is valid and will be supplied on request. All orders are accepted subject to our current general terms and conditions.

Edition: 17 March 2020

**SUITABILITY- AND PRE-TESTS ARE NECESSARY BEFORE APPLYING THE CONCRETE ADMIXTURE!**